

APLICAÇÃO

Luminária de sobrepor.

ESTRUTURA

Luminária comercial de sobrepor, corpo em chapa de aço tratada e fosfatizada com pintura eletrostática em epóxi-pó na cor branco fosco, com refletância de 92%. – Grau de Proteção IP20.

SISTEMA ÓTICO

Difusor Translúcido com transmitância de 88%.

EQUIPAMENTOS ELÉTRICOS

Equipada com módulos de LED com LM80, que possuem LM70 para TM-21, atendendo aos requisitos mínimos do DLC (Design Lighting Consortium) garantindo a LM-79 para a luminária. Com opções 220V, Bi-Volt e Dimerizável (0-10V).

INFORMAÇÕES TÉCNICAS

W 18,4 W

 3000 / 4000 / 5000K


 >80

 220V

 1,922 lm

 5 ANOS

CURVA FOTOMÉTRICA



ÍNDICE DE OFUSCAMENTO UNIFICADO - UGR

Glare Evaluation According to UGR													
Room Size		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis						
X	Y	2H	3H	4H	6H	8H	12H	2H	3H	4H	6H	8H	12H
2H	2H	18.5	19.8	18.8	20.0	20.3	18.3	19.5	18.6	19.8	20.0	20.0	20.0
2H	3H	20.2	21.3	20.5	21.6	21.8	19.9	21.1	20.2	21.3	21.6	21.6	21.6
4H	4H	20.8	21.9	21.1	22.1	22.4	20.5	21.6	20.9	21.9	22.2	22.2	22.2
4H	6H	21.2	22.2	21.6	22.5	22.8	21.0	22.0	21.3	22.3	22.6	22.6	22.6
4H	8H	21.4	22.3	21.7	22.6	23.0	21.1	22.1	21.5	22.4	22.7	22.7	22.7
4H	12H	21.4	22.4	21.8	22.7	23.0	21.2	22.1	21.6	22.4	22.8	22.8	22.8
4H	2H	19.0	20.1	19.4	20.4	20.7	18.8	19.9	19.2	20.2	20.5	20.5	20.5
4H	3H	20.9	21.8	21.3	22.1	22.5	20.7	21.6	21.0	21.9	22.3	22.3	22.3
4H	4H	21.6	22.5	22.0	22.8	23.2	21.4	22.3	21.8	22.6	23.0	23.0	23.0
4H	6H	22.2	22.9	22.6	23.3	23.7	22.0	22.7	22.4	23.1	23.5	23.5	23.5
4H	8H	22.4	23.1	22.8	23.5	23.9	22.2	22.9	22.7	23.3	23.7	23.7	23.7
4H	12H	22.5	23.1	23.0	23.5	24.0	22.4	22.9	22.8	23.4	23.8	23.8	23.8
8H	4H	21.9	22.6	22.3	23.0	23.4	21.7	22.4	22.2	22.8	23.2	23.2	23.2
8H	6H	22.6	23.2	23.1	23.6	24.0	22.5	23.0	22.9	23.4	23.9	23.9	23.9
8H	8H	22.9	23.4	23.4	23.8	24.3	22.7	23.2	23.2	23.6	24.1	24.1	24.1
8H	12H	23.1	23.5	23.6	24.0	24.5	22.9	23.3	23.4	23.8	24.3	24.3	24.3
12H	4H	21.9	22.5	22.4	22.9	23.4	21.8	22.4	22.2	22.8	23.2	23.2	23.2
12H	6H	22.7	23.2	23.2	23.6	24.1	22.5	23.0	23.0	23.4	23.9	23.9	23.9
12H	8H	23.0	23.4	23.5	23.9	24.4	22.8	23.2	23.3	23.7	24.2	24.2	24.2

Variation of the observer position for the luminaire distances S		
S = 1.0H	+0.1 / -0.1	+0.1 / -0.1
S = 1.5H	+0.2 / -0.4	+0.2 / -0.4
S = 2.0H	+0.4 / -0.7	+0.4 / -0.8


Standard table	BK05	BK05
Correction		
Summand	3.2	3.0

Corrected Glare Indices referring to 1920lm Total Luminous Flux

The UGR values have been calculated according to CIE Publ. 117 Spacing-to-Height-Ratio = 1.00.

DIAGRAMA DE CONE

Luminaire: LT-DIF.351.216.17
Lamps: 1 x 17W - 1,920LM - KIT 3



MODELO	INSTALAÇÃO	POTÊNCIA	TENSÃO	FLUXO LUM.	COMP.	LARGURA	ALTURA	NICHO
LT DIF 351 216 17	SOBREPOR	18,4 W	220V	1,922 Lm	617 mm	147 mm	91 mm	
LT DIF 351 216 B17	SOBREPOR	18,4 W	Bi-Volt	1,922 Lm	617 mm	147 mm	91 mm	
LT DIF 351 216 D17	SOBREPOR	18,4 W	220V (01-10V)	1,922 Lm	617 mm	147 mm	91 mm	
LT DIF 351 416 34	SOBREPOR	36,9 W	220V	3,844 Lm	617 mm	147 mm	91 mm	
LT DIF 351 416 B34	SOBREPOR	36,9 W	Bi-Volt	3,844 Lm	617 mm	147 mm	91 mm	
LT DIF 351 416 D34	SOBREPOR	36,9 W	220V (01-10V)	3,844 Lm	617 mm	147 mm	91 mm	
LT DIF 351 416 48	SOBREPOR	52,7 W	220V	5,126 Lm	617 mm	147 mm	91 mm	
LT DIF 351 416 D48	SOBREPOR	52,7 W	220V (01-10V)	5,126 Lm	617 mm	147 mm	91 mm	