



APLICAÇÃO

Luminária de sobrepor.

ESTRUTURA

Luminária comercial de embutir, corpo em chapa de aço tratada e fosfatizada com pintura eletrostática em epóxi-pó na cor branco fosco, com refletância de 92%. – Grau de Proteção IP54.






SISTEMA ÓTICO

Difusor Translúcido com transmitância de 88%.


EQUIPAMENTOS ELÉTRICOS

Equipada com módulos de LED com LM80, que possuem LM70 para TM-21, atendendo aos requisitos mínimos do DLC (Design Lighting Consortium) garantindo a LM-79 para a luminária. Com opções 220V, Bi-Volt e Dimerizável (0-10V).

INFORMAÇÕES TÉCNICAS

W	36,9 W
	3000 / 4000 / 5000K
	>80
	220V (01-10V)
	3,844 lm
	5 ANOS

CURVA FOTOMÉTRICA



ÍNDICE DE OFUSCAMENTO UNIFICADO - UGR


Glare Evaluation According to UGR											
p Ceiling		70	70	50	30	70	70	50	50	30	
p Walls		50	30	50	30	50	30	50	30	30	
p Floor		20	20	20	20	20	20	20	20	20	
Room Size X	Room Size Y	Viewing direction at right angles to lamp axis				Viewing direction parallel to lamp axis					
2H	2H	16.9	18.2	17.2	18.5	18.7	16.7	18.0	17.0	18.2	18.5
	3H	18.6	19.8	18.9	20.1	20.3	18.4	19.6	18.7	19.8	20.1
	4H	19.3	20.4	19.6	20.7	21.0	19.0	20.2	19.4	20.4	20.7
	6H	19.8	20.8	20.1	21.1	21.4	19.6	20.6	19.9	20.9	21.2
	8H	20.0	21.0	20.3	21.3	21.6	19.8	20.8	20.1	21.1	21.4
4H	12H	20.1	21.1	20.5	21.4	21.7	19.9	20.8	20.3	21.2	21.5
	2H	17.4	18.6	17.8	18.8	19.1	17.2	18.4	17.6	18.6	18.9
	3H	19.4	20.3	19.7	20.6	21.0	19.2	20.1	19.5	20.4	20.8
	4H	20.2	21.0	20.6	21.4	21.7	20.0	20.8	20.4	21.2	21.6
	6H	20.8	21.6	21.2	21.9	22.3	20.6	21.4	21.1	21.8	22.2
8H	12H	21.1	21.8	21.5	22.2	22.6	20.9	21.6	21.3	22.0	22.4
	2H	21.3	21.9	21.7	22.3	22.7	21.1	21.7	21.6	22.1	22.6
	4H	20.5	21.1	20.9	21.5	22.0	20.3	21.0	20.7	21.4	21.8
	6H	21.3	21.8	21.7	22.3	22.7	21.1	21.7	21.6	22.1	22.6
	8H	21.6	22.1	22.1	22.6	23.0	21.5	22.0	22.0	22.4	22.9
12H	12H	21.9	22.3	22.4	22.8	23.3	21.8	22.2	22.3	22.7	23.2
	4H	20.5	21.1	20.9	21.5	22.0	20.3	21.0	20.8	21.4	21.8
	6H	21.4	21.9	21.8	22.3	22.8	21.2	21.7	21.7	22.2	22.6
	8H	21.7	22.2	22.2	22.6	23.1	21.6	22.0	22.1	22.5	23.0
	12H	21.7	22.2	22.2	22.6	23.1	21.6	22.0	22.1	22.5	23.0

Variation of the observer position for the luminaire distances S		
S = 1.0H	+0.1 / -0.1	+0.1 / -0.1
S = 1.5H	+0.2 / -0.4	+0.2 / -0.4
S = 2.0H	+0.4 / -0.7	+0.4 / -0.7
Standard table Correction Summand	BK06 -0.1	BK06 -0.3

Corrected Glare Indices referring to 3940lm Total Luminous Flux

The UGR values have been calculated according to CIE Publ. 117 Spacing-to-Height-Ratio = 0.25.

DIAGRAMA DE CONE



MODELO	INSTALAÇÃO	POTÊNCIA	TENSÃO	FLUXO LUM.	COMP.	LARGURA	ALTURA	NICHO
LT IPI 3554 232 17	EMBUTIR	18,4 W	220 V	1,922 Lm	1256 mm	263 mm	69 mm	1244 X 251
LT IPI 3554 232 B17	EMBUTIR	18,4 W	Bi-Volt	1,922 Lm	1256 mm	263 mm	69 mm	1244 X 251
LT IPI 3554 232 D17	EMBUTIR	18,4 W	220V (01-10 V)	1,922 Lm	1256 mm	263 mm	69 mm	1244 X 251
LT IPI 3554 232 34	EMBUTIR	36,9 W	220 V	3,844 Lm	1256 mm	263 mm	69 mm	1244 X 251
LT IPI 3554 232 B34	EMBUTIR	36,9 W	Bi-Volt	3,844 Lm	1256 mm	263 mm	69 mm	1244 X 251
LT IPI 3554 232 D34	EMBUTIR	36,9 W	220V (01-10 V)	3,844 Lm	1256 mm	263 mm	69 mm	1244 X 251
LT IPI 3554 232 48	EMBUTIR	52,7 W	220 V	5,126 Lm	1256 mm	263 mm	69 mm	1244 X 251
LT IPI 3554 232 D48	EMBUTIR	52,7 W	220V (01-10 V)	5,126 Lm	1256 mm	263 mm	69 mm	1244 X 251